

Access Control
Video Surveillance
Payroll
Time Attendance
Workforce Management

ESG Governance & Net Zero 2050

Scalability & Sustainability

Smart Building Solution

Jakin ID

ACTatek Unified Platform

Managing People · Security · Environment · Energy



The ACTatek model AT-3K-FA-FSMA-P is designed for hassle-free installation and seamless integration. It offers multi-factor authentication with facial, fingerprint, RFID cards, QR code and PIN as credentials, ensuring flexible and secure access.

It's also a CCTV at your door, streaming live video and capturing 2.0 Megapixel high-resolution images as part of the event log. With integrated intrusion detection, the device can identify presence and loitering near entry points, providing proactive alerts before intrusion occurs. This combination of video surveillance and intelligent sensing enhances situational awareness and security for businesses and intelligent buildings.

The ACTatek device is secured with advanced TLS 1.3 encryption with regular updates for cybersecurity. Its IP65 weather rating ensures reliable outdoor performance, while the IK10 casing provides high resistance to physical impact, extending durability and protection in demanding environments.

FCCE UK CA IK10 IEC 62368-1

IP65 (Water Proof & Impact Resistant)

FROST & SULLIVAN


"2010 World Biometrics Vertical Market Penetration Leadership Award"



Google 2-Factor Authentication adds protection, while QR code integration simplifies user access. The device features built-in PoE, minimizing the need for extensive cabling and effectively reducing installation complexity and its carbon footprint, while aligning with ESG and NetZero goals.

One System. Total Control

ACTAtek™



Standard Features

Model Options: AT-3K-FA-FSMA-P

FingerPrint authentication	✓
Built-in smartcard reader	✓
Facial recognition with camera	✓
QR code authentication with camera	✓
Built-in web and database server	Web-Based
Built-in IR distance sensor and LED	✓
Number of users	3,000 users
Number of Event Logs	1,000K (FIFO when is full)
Static IP address assignment	✓
Dynamic IP address assignment	✓
Power Over Ethernet	IEEE 802.3af/at/bt
Valid characters for employee ID	0-9, A-C (max. 16 characters)
Programmable function keys support	F1,F2,F3,F4
Authentication time	< 1 second
FingerPrint Users capacity	3,000(1:1) / 3,000(1:N)
Face Users capacity	3,000(1:1) / 3,000(1:N)
Alert	by email and SMS, LCD message displayed
WiFi (Optional)	IEEE 802.11 a/b/g/n/ac
SIM Card LTE/4G	Optional
IP Intercom (Built-in)	Optional (SIP, VoIP Intercom)
Body Temperature Sensor (Temsens) (Optional)	Specification: Power supply: 12VDC from ACTAtek device Measuring range: 35.0 C - 42.8 C Fever alert: 38.0 C - 42.8C Red LED Blinks Measuring distance: 100mm - 250mm Accuracy: +/- 0.2C Speed: 600mS Interface: RS232

Model Options: AT-3K-FA-FSMA-P

Cyber Security	✓ HTTP/HTTPS encrypted communications ✓ TLS1.3 256-bit with periodic updates ✓ IP range restrictions ; Allowed IP ✓ OWASP VAPT report (Vulnerability Assessment and Penetration Testing)
Remote Enrollment (Facial/Smart Card/PIN)	✓
Remote Clock-in-out	✓
SNMP Version 3 (Simple Network Management Protocol)	✓
Multi-lingual support	✓
Network interface (Built-in)	1,000 BaseT Ethernet
I/O interface	- RS-232 / RS-485 - Wiegand output (26bit)
Operation temperature	-40 °C to 60 °C
RFID cards support (*Smart Card model)	MiFare, MiFare Plus
Modes of authentications (depending on device model: single or multi-factor authentication)	Facial, FingerPrint, Smart Card, PIN, QR code Facial+FingerPrint; Smart Card+FingerPrint QR Code+FingerPrint; Smart Card+PIN Facial+Google Passcode FingerPrint+Google Passcode QR code+Google Passcode *Google Authenticator App is required for Google Passcode
Relay/Door Switch/Door Bell	1 relay /1 door switch/1 door bell
Safety standard/Casing	CE ,FCC ,IK 10 ,IEC 62368-1 ,UKCA IP65-fluid ingress,dust,salt,fog protection
Product Life Cycle	Minimum 10 years
Components	Industrial grade components only to guarantee wide operating temperature, reliability and durability of the device