

ACTatek SOAP API Manual



Version 1.23

ACTatek (UK) Ltd.

Last Update :2025.December



ACTAtetek SOAP API Manual

Copyright 2025 ACTAtetek (UK) Ltd, All rights reserved.

No part of this document may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual or otherwise without the prior written permission of ACTAtetek (UK) Ltd.

ACTAtetek is a registered trademark of ACTAtetek (UK) Ltd

All trademarks, registered trademarks, and service marks are the property of their respective owners.

Offices:

Asia and the Rest of the World:

Unit 913-914, 9/F., Worldwide Industrial Centre, 43-47 Shan Mei Street, Fotan, Shatin, N.T., Hong Kong

Tel: (852) 2319 1333

E-mail: info@actatek.com

America:

ACTAtetek Technologies Inc.
411-1221 HOMER ST,VANCOUVER BC V6B 1C5,Canada

Phone: (+1) 604 314 7628

E-mail: info@actatek.com

Europe:

ACTAtetek (UK) Ltd.
118 Pall Mall, London SW1Y 5EA, U.K.

Phone: (44) 7344 2638 81

E-mail: info@actatek.com

Table of Contents

Chapter 1.Introduction.....	1
1.1.Prerequisite.....	1
1.2.Coverage.....	1
1.3.SOAP.....	1
1.4.Web Service Definition Language (WSDL).....	1
Chapter 2.SOAP API Reference.....	2
2.1.Datatype Definition.....	2
2.1.1.Status.....	2
2.1.2.Fingerprint.....	2
2.1.3.FingerprintArray.....	3
2.1.4.Department.....	3
2.1.5.DepartmentArray.....	3
2.1.6.Weekday.....	3
2.1.7.Timespec.....	3
2.1.8.AccessRight.....	4
2.1.9.Group.....	4
2.1.10.GroupArray.....	4
2.1.11.AdminLevel.....	4
2.1.12.FingerprintSecurityLevel.....	5
2.1.13.User.....	5
2.1.14.UserArray.....	5
2.1.15.userID.....	6
2.1.16.UserIDArray.....	6
2.1.17.TriggerType.....	6
2.1.18.Trigger.....	6
2.1.19.TriggerArray.....	6
2.1.20.eventType.....	7
2.1.21.Log.....	8
2.1.22.LogArray.....	8
2.1.23.LogDetail.....	8
2.1.24.LogDetailArray.....	8
2.1.25.getLogCriteria.....	9
2.1.26.getUserCriteria.....	9
2.1.27.getGroupsCriteria.....	9
2.1.28.getTriggersCriteria.....	9
2.1.29.Agent.....	10
2.1.30.AgentArray.....	10
2.1.31.TerminalStatus.....	10

2.1.32.Terminal.....	11
2.1.33.TerminalArray.....	11
2.1.34.AutoInOutOption.....	11
2.1.35.RelayID.....	11
2.1.36.RelayOption.....	12
2.1.37.JobCodeSettings.....	12
2.1.38.JobCodeSettingsArray.....	12
2.1.39.JobCode.....	13
2.1.40.JobCodeArray.....	13
2.1.41.Holiday.....	14
2.1.42.HolidayArray.....	15
2.1.43.Holidays.....	15
2.1.44.FacialArray.....	16
2.1.45.Facial.....	16
2.1.46 LogEvent.....	17
2.1.47 LogSize.....	17
2.1.48 EM-Log-Option.....	17
2.1.49 LogSetting.....	18
2.2.SOAP API.....	19
2.2.1.Session Establishment.....	19
2.2.2.Log Management	20
2.2.3.User Management.....	22
2.2.4.Department Management.....	35
2.2.5.Access Group Management	38
2.2.6.Trigger Maintenance Functions.....	41
2.2.7.Personal Functions.....	43
2.2.8.Agent.....	45
2.2.9.Time Settings.....	47
2.2.10.Misc Functions.....	53
2.2.11.Terminal Settings.....	57
2.2.12.Job Code.....	65
2.2.13.Consent.....	71
2.2.14.Log Setting.....	72
Chapter 3.Creating C Application.....	74
3.1.Requirements.....	74
3.2.Example.....	74
Chapter 4.Creating Visual Basic Application.....	77
4.1.Requirements	77

4.2.Example.....	77
Chapter 5.Creating .NET Application.....	79
5.1.Requirements.....	79
5.2.Example.....	79
Chapter 6.Creating JAVA Application.....	82
6.1.Requirements.....	82
6.2.Example.....	82
Chapter 7.Using SOAP API with SSL.....	84
7.1.Requirements.....	84
7.2.Example.....	84
Appendix A. Door Open Schedule	88
Appendix B:Added a new element in the ns:User structure.....	89

Chapter 1. Introduction

1.1. Prerequisite

This document is intended for software engineers who have basic knowledge in programming, XML and TCP/IP network.

1.2. Coverage

This document will cover ACTAtek SOAP API functions provided by ACTAtek, and a brief description on WebService Proxy generation in different languages.

1.3. SOAP

SOAP provides a XML based infrastructure for exchanging structured and typed information between peers in a decentralized, distributed environment.

1.4. Web Service Definition Language (WSDL)

WSDL, in general, is an XML file describing the details of how to call the Web Service it provides. In ACTAtek, the WSDL file can be accessed through the following URL:

<http://<deviceIP>/soap/document/ACTAtek.wsdl>

Chapter 2. SOAP API Reference

Due to language independency of SOAP WebServices, the calling syntax would depend on the actual language for client implementation. Without loss of generosity, we would describe the API in terms of the function name, parameter name, parameter type, return parameter name, return type. In case of fault, the fault string will describe the what the actual problem is. For the exact definition, please refer the actual WSDL file.

General Flow of Operation

When you access any function, you need to give a session ID. The session ID can be obtained through the login function. You can execute multiple functions using the same session ID. The session ID would represent the login user during the execution process. When you finish using the service, you have to logout the session by giving the session ID for system cleanup, although, the system can expire the unused session ID for 30 minutes by default.

2.1. Datatype Definition

2.1.1. Status

Element	Type	Description
Active	xsd: boolean	
autoMatch	xsd: boolean	
smartcard	xsd: boolean	
fingerprint	xsd: boolean	
password	xsd: boolean	
facialAutoMatch	xsd: boolean	
facial	xsd: Boolean	

Table 1. .Status Data Type Definition

2.1.2. Fingerprint

Element	Type	Description
image	xsd:base64Binary	Fingerprint template

Table 2.Fingerprint Data Type Definition

2.1.3. *FingerprintArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
fingerprint	ns:fingerprint	Array of fingerprint templates

Table 3.FingerprintArray Data Type Definition

2.1.4. *Department*

<i>Element</i>	<i>Type</i>	<i>Description</i>
departmentID	xsd:int	
departmentName	xsd:string	
departmentDescription	xsd:string	

Table 4.Department Data Type Definition

2.1.5. *DepartmentArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
department	ns:Department	

Table 5.DepartmentArray Data Type Definition

2.1.6. *Weekday*

<i>Element</i>	<i>Type</i>	<i>Description</i>
Weekday	enum { SUNDAY, MONDAY, TUESDAY, WEDNESDAY, THURSDAY, FRIDAY, SATURDAY, HOLIDAY }	

Table 6.Weekday Data Type Definition

2.1.7. *Timespec*

<i>Element</i>	<i>Type</i>	<i>Description</i>
weekday	xsd:Weekday[]	
timePattern	xsd:string	

Table 7.Timespec Data Type Definition

Element: timePattern (string) (48-byte strings of '0'(off) and/or '1'(on))

Remark: First byte representing timeslot [00:00-00:29], 2nd byte [00:30-00:59] etc.

2.1.8. AccessRight

<i>Element</i>	<i>Type</i>	<i>Description</i>
accessID	xsd:int	
terminalSN	xsd:string	
quickAccess	xsd:boolean	
timeSpec	ns:Timespec	

Table 8.AccessRight Data Type Definition

2.1.9. Group

<i>Element</i>	<i>Type</i>	<i>Description</i>
groupID	xsd:int	
groupName	xsd:string	
departmentID	xsd:int	
accessRight	ns:AccessRight	

Table 9.Group Data Type Definition

2.1.10. GroupArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
group	ns:Group	

Table 10.GroupArray Data Type Definition

2.1.11. AdminLevel

<i>Element</i>	<i>Type</i>	<i>Description</i>
AdminLevel	xsd:enum { PERSONALUSER, NETWORKADMIN, USERADMIN, SUPERADMIN }	

Table 11.AdminLevel Data Type Definition

2.1.12. *FingerprintSecurityLevel*

<i>Element</i>	<i>Type</i>	<i>Description</i>
FingerprintSecurityLevel	xsd:enum { LOW, NORMAL, HIGH, HIGHEST }	

Table 12.FingerprintSecurityLevel Data Type Definition

2.1.13. *User*

<i>Element</i>	<i>Type</i>	<i>Description</i>
userID	xsd:string	User ID
lastName	xsd:string	Last name
firstName	xsd:string	First name
otherName	xsd:string	Other name
usePassword	xsd:boolean	Enable password verification
password	xsd:string	Password for login and verification
adminLevel	ns:AdminLevel	Administration level
groupID	xsd:int[]	Access Group ID
departmentID	xsd:int[]	Department ID
fingerprintSecurityLevel	ns:FingerprintSecurityLevel	Fingerprint security level
status	ns:Status	
fingerprints	ns:Fingerprint[]	Array of fingerprint template
cardsn	xsd:string	Smartcard serial number
fpgroupid	xsd:int	FP group id max value of 255
facialrecords	ns:Facial[]	Array of facial template

Table 13.User Data Type Definition

2.1.14. *UserArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
user	ns:User	

Table 14.UserArray Data Type Definition

2.1.15. *userID*

<i>Element</i>	<i>Type</i>	<i>Description</i>
userID	xsd:string	User ID

Table 15.userID Data Type Definition

2.1.16. *UserIDArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
uids	ns:userID	

Table 16.UserIDArray Data Type Definition

2.1.17. *TriggerType*

<i>Element</i>	<i>Type</i>	<i>Description</i>
triggerType	xsd:enum { _UNKNOWN, _IN, _OUT, _F1, _F2, _F3, _F4, _F5, _F6, _F7, _F8, _F9, _F10 }	

Table 17.TriggerType Data Type Definition

2.1.18. *Trigger*

<i>Element</i>	<i>Type</i>	<i>Description</i>
triggerType	xsd:triggerType	
triggerName	xsd:string	
timeSpec	xsd:Timespec	

Table 18.Trigger Data Type Definition

2.1.19. *TriggerArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
trigger	ns:Trigger	

Table 19.TriggerArray Data Type Definition

2.1.20. eventType

<i>Element</i>	<i>Type</i>	<i>Description</i>
eventType	enum: { UNKNOWN, IN, OUT, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, ID_UNKNOWN, REJECTED, ID_RESERVED, RESET_ALL, RESET_ACC, RESET_DEVICE, RESET_PASSWORD, RESET_DEFAULT, SYSTEM_LOGIN, ADMIN_LOGIN, USER_LOGIN, NETWORK_CHANGE, PATCHED, BACKUP_DB, RESTORE_DB, SYSTEM_RSVD, ENROLL_USER, UPDATE_USER, REMOVE_USER, SUSPEND_USER, EDIT_EVENT, RESET_ADMIN_PW, ADMIN_RSVD }	

Table 20.eventType Data Type Definition

2.1.21. Log

<i>Element</i>	<i>Type</i>	<i>Description</i>
logID	xsd:long	
userID	xsd:string	
timestamp	xsd:dateTime	
trigger	xsd:eventType	
terminalSN	xsd:string	

Table 21.Log Data Type Definition

2.1.22. LogArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
log	ns:Log	

Table 22.LogArray Data Type Definition

2.1.23. LogDetail

<i>Element</i>	<i>Type</i>	<i>Description</i>
logID	xsd:long	
userID	xsd:string	
userName	xsd:string	[first name] [last name]
departmentName	xsd:string	
timestamp	xsd:dateTime	
trigger	xsd:eventType	
terminalSN	xsd:string	
terminalName	xsd:string	
jpegPhoto	xsd:base64binary	
remark	xsd:string	

Table 23.LogDetail Data Type Definition

2.1.24. LogDetailArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
log	ns:LogDetail	

Table 24.LogDetailArray Data Type Definition

2.1.25. *getLogsCriteria*

<i>Element</i>	<i>Type</i>	<i>Description</i>
from	xsd:dateTime	
to	xsd:dateTime	
employeeName	xsd:string	
employeeID	xsd:string	
departmentID	xsd:int	
trigger	xsd:eventType	
terminalSN	xsd:string	

Table 25.getLogsCriteria Data Type Definition

2.1.26. *getUsersCriteria*

<i>Element</i>	<i>Type</i>	<i>Description</i>
userID	xsd:string	
partialUserID	xsd:string	
lastName	xsd:string	
firstName	xsd:string	
otherName	xsd:string	
departmentID	xsd:int	

Table 26.getUsersCriteria Data Type Definition

2.1.27. *getGroupsCriteria*

<u><i>Element</i></u>	<u><i>Type</i></u>	<u><i>Description</i></u>
<u>groupID</u>	<u>xsd:int</u>	
<u>departmentID</u>	<u>xsd:int</u>	

Table 27.getGroupsCriteria Data Type Definition

2.1.28. *getTriggersCriteria*

<i>Element</i>	<i>Type</i>	<i>Description</i>
triggerType	ns:triggerType	

Table 28.getTriggersCriteria Data Type Definition

2.1.29. Agent

<i>Element</i>	<i>Type</i>	<i>Description</i>
port	xsd:int	
ip	xsd:string	
registrationTime	xsd:dateTime	
lastUpdate	xsd:dateTime	
lastCheck	xsd:dateTime	
lastCheckStatus	xsd:boolean	
active	xsd:boolean	
link	xsd:string	

Table 29.Agent Data Type Definition

2.1.30. AgentArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
agents	ns:Agent	

Table 30.AgentArray Data Type Definition

2.1.31. TerminalStatus

<i>Element</i>	<i>Type</i>	<i>Description</i>
modelNumber	xsd:string	
serialNumber	xsd:string	
firmwareVersion	xsd:string	
FAMVersion	xsd:string	
description	xsd:string	
registeredUsers	xsd:int	
maximumUsers	xsd:int	
automatchUsers	xsd:int	
maximumAutomatchUsers	xsd:int	

Table 31.TerminalStatus Data Type Definition

2.1.32. Terminal

<i>Element</i>	<i>Type</i>	<i>Description</i>
terminalID	xsd:int	
terminalType	xsd:string	
terminalName	xsd:string	
terminalSN	xsd:string	
terminalIP	xsd:string	

Table 32. Terminal Data Type Definition

2.1.33. TerminalArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
terminal	ns:Terminal	
size	int	

Table 33. TerminalArray Data Type Definition

2.1.34. AutoInOutOption

<i>Element</i>	<i>Type</i>	<i>Description</i>
AutoInOutOption	enum: { DISABLE, ENABLE, SPECIAL, REJECTREPEATEDLOGIN }	

Table 34. AutoInOutOption Data Type Definition

2.1.35. RelayID

<i>Element</i>	<i>Type</i>	<i>Description</i>
RelayID	enum: { ONE, TWO, ALL }	

Table 35. RelayID Data Type Definition

2.1.36. *RelayOption*

<i>Element</i>	<i>Type</i>	<i>Description</i>
RelayOption	enum: { RELAY-DISABLE, ACCESS-GRANTED, ACCESS-DENIED, DOORBELL, BELLSCHEDULE }	Relay One only able to set RELAY-DISABLE or ACCESS-GRANTED

Table 36. RelayOption Data Type Definition

2.1.37. *JobCodeSettings*

<i>Element</i>	<i>Type</i>	<i>Description</i>
jobcode	xsd : int	
jobcodeName	xsd : string	Name or Description
enable	xsd : int	

Table 37. JobCodeSettings Data Type Definition

2.1.38. *JobCodeSettingsArray*

<i>Element</i>	<i>Type</i>	<i>Description</i>
ptrjobcodesettings	ns : JobCodeSettings	Array of JobCodeSettings
size	xsd : int	Size of Array

Table 38. JobCodeSettingsArray Data Type Definition

2.1.39. JobCode

<i>Element</i>	<i>Type</i>	<i>Description</i>
JobCodeID	xsd : int	Int value minimum value of 1 maximum of 999999
JobCodeDescription	xsd : string	Description
enable	xsd : int	Bit 0: <ul style="list-style-type: none"> • 0 : IN • 1 : OUT Bit 1: <ul style="list-style-type: none"> • 0 : Normal • 1 : Default Bit 2: <ul style="list-style-type: none"> • 0 : Enabled • 1 : Disabled
jobcode	xsd : int	Jobcode value from jobcodesettings

Table 39.JobCode Data Type Definition

2.1.40. JobCodeArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
ptrjobcodes	ns : JobCode	Array of JobCode
size	xsd : string	Size of Array

Table 40.JobCodeArray Data Type Definition

2.1.41. Holiday

Element	Type	Description
HolidayDay	xsd : int	Day (1-31), 0 for wildcard in HolidayCriteria
HolidayMonth	xsd : int	Month(1-12), 0 for wildcard in HolidayCriteria
HolidayYear	xsd : int	Year(1900-9999), 0 for wildcard in HolidayCriteria

Table 41.Holiday Data Type Definition

2.1.42. HolidayArray

Element	Type	Description
ptrholidays	ns:Holiday	Array of Holiday
size	xsd : int	Size of Array

Table 42.HolidayArray Data Type Definition

2.1.43 Holidays

2.1.43.1 getHolidays

2.1.43.1.1 Arguments

sessionID, xsd:long

HolidayCriteria, xsd:Holiday

2.1.43.1.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getHolidays>
      <sessionID>0</sessionID>
      <HolidayCriteria>
        <HolidayDay>0</HolidayDay>
        <HolidayMonth>0</HolidayMonth>
        <HolidayYear>0</HolidayYear>
      </HolidayCriteria>
    </ns:getHolidays>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.1.43.1.3 Return

getHolidayArray: ns:HolidayArray

2.1.43.2 setHolidays

2.1.43.2.1 Arguments

sessionID, xsd:long
 setHolidayArray, xsd:HolidayArray

2.1.43.2.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setHolidays>
      <sessionID>0</sessionID>
      <setHolidayArray>
        <holidays>
          <HolidayDay>0</HolidayDay>
          <HolidayMonth>0</HolidayMonth>
          <HolidayYear>0</HolidayYear>
        </holidays>
      </setHolidayArray>
    </ns:setHolidays>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.1.43.2.3 Return

status: xsd:string

2.1.43.3 deleteHolidays

2.1.43.3.1 Arguments

sessionID, xsd:long
 deleteHolidayArray, xsd:HolidayArray

2.1.43.3.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:deleteHolidays>
      <sessionID>0</sessionID>
      <deleteHolidayArray>
        <holidays>
```

```

    <HolidayDay>0</HolidayDay>
    <HolidayMonth>0</HolidayMonth>
    <HolidayYear>0</HolidayYear>
  </holidays>
</deleteHolidayArray>
</ns:deleteHolidays>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.1.43.3.4 Return
status: xsd:string

2.1.44 FacialArray

<i>Element</i>	<i>Type</i>	<i>Description</i>
facial	ns:Facial	Array of facial templates

Table 43. FingerprintArray Data Type Definition

2.1.45 Facial

<i>Element</i>	<i>Type</i>	<i>Description</i>
FacialTemplateType	xsd:int	Type of template 0: NOT DEFINED 1: FLI fingerprint(not for facial) 2: 3DIVI_8V6
FacialTemplate	xsd:base64Binary	Facial template

Table 44. Facial Data Type Definition

2.1.46 LogEvent

<i>Element</i>	<i>Type</i>	<i>Description</i>
LogEvent	enum { LOGEVENT-DISABLE, LOGEVENT-USER, LOGEVENT-AUDIT, LOGEVENT-USER_AUDIT }	LOGEVENT-DISABLE: disable event log LOGEVENT-USER:Log user event LOGEVENT-AUDIT:Log audit event LOGEVENT-USER_AUDIT: log user and audit event

2.1.47 LogSize

<i>Element</i>	<i>Type</i>	<i>Description</i>
LogSize	enum { LOGS-10K, LOGS-75K, LOGS-100K, LOGS-500K, LOGS-1000K }	LOGS-10K,: 10000 logs LOGS-75K: 75000 logs LOGS-100K: 100000 logs LOGS-500K: 500000 logs LOGS-1000K: 1000000 logs

2.1.48 EM-Log-Option

<i>Element</i>	<i>Type</i>	<i>Description</i>
EM-Log-Option	enum { EM-LOG-FULL-SN, EM-LOG-ID-ONLY, EM-LOG-FC-ID }	EM-LOG-FULL-SN: use full sn in event log remark EM-LOG-ID-ONLY: use EM ID in event log remark EM-LOG-FC-ID: user FC+ID in event log remark

2.1.49 LogSetting

<i>Element</i>	<i>Type</i>	<i>Description</i>
log-event	ns LogEvent	Mode of Log event
log-size	ns LogSize	Max logs stored in device
log-unAuth-event	xsd:boolean	True will log all unauthorized event
log-Accept-nonRegistered-card	xsd:boolean	True will accept all non-registered card if supported
log-photo-Auth-event	xsd:boolean	True will save photo in authorized event
log-photo-unAuth-event	xsd:boolean	True will save photo in unauthorized event
log-Accept-nonRegistered-facial	xsd:boolean	True will accept all non-registered face if supported
log-case-event	xsd:boolean	True wil save the case open/close event
log-EM-Option	ns EM-Log-Option	Optional: The remarks field setting if using EM model

2.2. SOAP API

2.2.1. Session Establishment

2.2.1.1. login

2.2.1.1.1. Arguments

- **username**, xsd:string
- **password**, xsd:string

2.2.1.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:login>
      <username></username>
      <password></password>
    </ns:login>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.1.1.3. Return

- **sessionID**, xsd: long

2.2.1.2. logout

2.2.1.2.1. Arguments

- **sessionID**, xsd:long

2.2.1.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```

xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:logout>
    <sessionID>0</sessionID>
  </ns:logout>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.1.2.3. Return

- **status**, xsd: string

2.2.2. Log Management

2.2.2.1. getLogs

2.2.2.1.1. Arguments

- **sessionID**, xsd:long
- **getLogsCriteria**, xsd:getLogsCriteria

2.2.2.1.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getLogs>
      <sessionID>0</sessionID>
      <getLogsCriteria>
        <from>2005-08-22T10:25:59Z</from>
        <to>2005-08-22T10:25:59Z</to>
        <employeeName></employeeName>
        <employeeID></employeeID>
        <departmentID>0</departmentID>
        <trigger>UNKNOWN</trigger>
        <terminalSN></terminalSN>
      </getLogsCriteria>
    </ns:getLogs>

```

```
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.2.1.3. Return

- `logs`, `xsd:LogArray[]`

2.2.2.2. `getFullLogs`

2.2.2.2.1. Arguments

- `sessionID`, `xsd:long`
- `getLogsCriteria`, `xsd:getLogsCriteria`

2.2.2.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getFullLogs>
      <sessionID>0</sessionID>
      <getLogsCriteria>
        <from>2006-09-22T09:30:08Z</from>
        <to>2006-09-22T09:30:08Z</to>
        <employeeName></employeeName>
        <employeeID></employeeID>
        <departmentID>0</departmentID>
        <trigger>UNKNOWN</trigger>
        <terminalSN></terminalSN>
      </getLogsCriteria>
      <limit>0</limit>
    </ns:getFullLogs>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.2.2.3. Return

- `logs`, `xsd:LogDetailArray[]`

2.2.2.3. **getLogPhoto**

2.2.2.3.1. **Arguments**

- **sessionID**, xsd:long
- **terminalSN**, xsd:string
- **timestamp**, xsd:dateTime

2.2.2.3.2. **WSDL**

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getLogPhoto>
      <sessionID>0</sessionID>
      <terminalSN></terminalSN>
      <timestamp></timestamp>
    </ns:getLogPhoto>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.2.3.3. **Return**

- **jpegPhoto**, xsd:base64Binary

2.2.2.4. **addLog**

2.2.2.4.1. **Arguments**

- **sessionID**, xsd:long
- **timestamp**, xsd:dateTime
- **employeeID**, xsd:string
- **event**, xsd:eventType
- **terminalSN**, xsd:string

2.2.2.4.2. **WSDL**

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
```

```

xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:addLog>
    <sessionID>0</sessionID>
    <timestamp></timestamp>
    <employeeID></employeeID>
    <event>UNKNOWN</event>
    <terminalSN></terminalSN>
  </ns:addLog>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.2.4.3. Return

- **status**, xsd:string

2.2.2.5. deleteLogs

(since 29.11)

Delete all logs, keeping only those added since *daysToKeep* days from today (00:00:00, local time today).

2.2.2.5.1. Arguments

- **sessionID**, xsd:long
- **daysToKeep**, the number of days from today, the logs will not be deleted. It cannot be > 366. Value of 0 will not delete those logs added today. To delete all logs use resetLog

2.2.2.5.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:deleteLogs>
      <sessionID>0</sessionID>
      <daysToKeep>0</daysToKeep>
    </ns:deleteLogs>
  </SOAP-ENV:Body>

```

```
</SOAP-ENV:Envelope>
```

2.2.2.5.3. Return

- **status**, xsd:string

2.2.2.6. resetLog

2.2.2.6.1. Arguments

- **sessionID**, xsd:long

2.2.2.6.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:resetLog>
      <sessionID>0</sessionID>
    </ns:resetLog>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.2.6.3. Return

- **status**, xsd:string

2.2.3. User Management

2.2.3.1. addUser

2.2.3.1.1. Arguments

- **sessionID**, xsd:long
- **user**, xsd:User

2.2.3.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```

xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:addUser>
    <sessionID>0</sessionID>
    <user>
      <userID></userID>
      <lastName></lastName>
      <firstName></firstName>
      <otherName></otherName>
      <adminLevel>PERSONALUSER</adminLevel>
      <usePassword>>false</usePassword>
      <password></password>
      <groupID>0</groupID>
      <departmentID>0</departmentID>
      <fingerprintSecurityLevel>LOW</fingerprintSecurityLevel>
      <status>
        <active>>false</active>
        <autoMatch>>false</autoMatch>
        <smartCard>>false</smartCard>
        <fingerprint>>false</fingerprint>
        <password>>false</password>
      </status>
      <fingerprints>
        <fingerprint>
          <image></image>
        </fingerprint>
      </fingerprints>
      <cardsn></cardsn>
    </user>
  </ns:addUser>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.1.3. Return

- **userID**, xsd:string

2.2.3.2. addUsers

2.2.3.2.1. Arguments

- **sessionID**, xsd:long
- **users**, xsd:UserArray

2.2.3.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
<ns:addUsers>
<sessionID>0</sessionID>
<users>
<user>
<userID></userID>
<lastName></lastName>
<firstName></firstName>
<otherName></otherName>
<adminLevel>PERSONALUSER</adminLevel>
<usePassword>>false</usePassword>
<password></password>
<groupID>0</groupID>
<departmentID>0</departmentID>
<fingerprintSecurityLevel>LOWEST</fingerprintSecurityLevel>
<status>
<active>>false</active>
<autoMatch>>false</autoMatch>
<smartCard>>false</smartCard>
<fingerprint>>false</fingerprint>
<password>>false</password>
</status>
<fingerprints
<fingerprint>
<image></image>
```

```

    </fingerprint>
  </fingerprints>
  <cardsn></cardsn>
</user>
</users>
</ns:addUsers>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.2.3. Return

- **uids**, xsd:UserIDArray

2.2.3.3. getUsers

2.2.3.3.1. Arguments

- **sessionID**, xsd:long
- **getUsersCriteria**, xsd:getUsersCriteria

2.2.3.3.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getUsers>
      <sessionID>0</sessionID>
      <getUsersCriteria>
        <userID></userID>
        <partialUserID></partialUserID>
        <lastName></lastName>
        <firstName></firstName>
        <otherName></otherName>
        <departmentID>0</departmentID>
      </getUsersCriteria>
    </ns:getUsers>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.3.3. Return

- **users**, xsd:UserArray

2.2.3.4. updateUser

2.2.3.4.1. Arguments

- **sessionID**, xsd:long
- **userID**, xsd:string
- **user**, xsd:User

2.2.3.4.2. WSDL

```
<<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:updateUser>
      <sessionID>0</sessionID>
      <userID></userID>
      <user>
        <userID></userID>
        <lastName></lastName>
        <firstName></firstName>
        <otherName></otherName>
        <adminLevel>PERSONALUSER</adminLevel>
        <usePassword>>false</usePassword>
        <password></password>
        <groupID>0</groupID>
        <departmentID>0</departmentID>
        <fingerprintSecurityLevel>LOW</fingerprintSecurityLevel>
        <status>
          <active>>false</active>
          <autoMatch>>false</autoMatch>
          <smartCard>>false</smartCard>
          <fingerprint>>false</fingerprint>
          <password>>false</password>
        </status>
        <fingerprints
```

```

<fingerprint>
  <image></image>
</fingerprint>
</fingerprints>
<cardsn></cardsn>
</user>
</ns:updateUser>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.4.3. Return

- **status**, xsd:string

2.2.3.5. updateUsers

2.2.3.5.1. Arguments

- **sessionID**, xsd:long
- **uids**, xsd:UserIDArray
- **users**, xsd:UserArray

2.2.3.5.2. WSDL

```

<<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:updateUsers>
    <sessionID>0</sessionID>
    <uids>
      <userID>
        <userID></userID>
      </userID>
    </uids>
    <users>
      <user>
        <userID></userID>
        <lastName></lastName>
        <firstName></firstName>

```

```

<otherName></otherName>
<adminLevel>PERSONALUSER</adminLevel>
<usePassword>>false</usePassword>
<password></password>
<groupID>0</groupID>
<departmentID>0</departmentID>
<fingerprintSecurityLevel>LOWEST</fingerprintSecurityLevel>
<status>
  <active>>false</active>
  <autoMatch>>false</autoMatch>
  <smartCard>>false</smartCard>
  <fingerprint>>false</fingerprint>
  <password>>false</password>
</status>
<fingerprints
  <fingerprint>
    <image></image>
  </fingerprint>
</fingerprints>
<cardsn></cardsn>
</user>
</users>
</ns:updateUsers>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.5.3. Return

- **status**, xsd:string

2.2.3.6. deleteUser

2.2.3.6.1. Arguments

- **sessionID**, xsd:long
- **userID**, xsd:string

2.2.3.6.2. WSDL

```

?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"

```

```

xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:deleteUser>
    <sessionID>0</sessionID>
    <userID></userID>
  </ns:deleteUser>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.6.3. Return

- **status**, xsd:string

2.2.3.7. activateUser

2.2.3.7.1. Arguments

- **sessionID**, xsd:long
- **userID**, xsd:string

2.2.3.7.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:activateUser>
      <sessionID>0</sessionID>
      <userID></userID>
    </ns:activateUser>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.7.3. Return

- **status**, xsd:string

2.2.3.8. deactivateUser

2.2.3.8.1. Arguments

- **sessionID**, xsd:long

- **userID**, xsd:string

2.2.3.8.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:deactivateUser>
      <sessionID>0</sessionID>
      <userID></userID>
    </ns:deactivateUser>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.3.8.3. Return

- **status**, xsd:string

2.2.3.9. getUserMessage

2.2.3.9.1. Arguments

- **sessionID**, xsd:long
- **userID**, xsd:string

2.2.3.9.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getUserMessage>
      <sessionID>0</sessionID>
      <userID></userID>
    </ns:getUserMessage>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.3.9.3. Return

- **message**, xsd:string

2.2.3.10. updateUserMessage**2.2.3.10.1. Arguments**

- **sessionID**, xsd:long
- **userID**, xsd:string
- **message**, xsd:string

2.2.3.10.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:updateUserMessage>
      <sessionID>0</sessionID>
      <userID></userID>
      <message></message>
    </ns:updateUserMessage>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.3.10.3. Return

- **status**, xsd:string

2.2.3.11. deleteUserMessage**2.2.3.11.1. Arguments**

- **sessionID**, xsd:long
- **userID**, xsd:string

2.2.3.11.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```

xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:deleteUserMessage>
    <sessionID>0</sessionID>
    <userID></userID>
  </ns:deleteUserMessage>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.11.3. Return

- **status**, xsd:string

2.2.3.12. getUserCount

2.2.3.12.1. Arguments

- **sessionID**, xsd:long

2.2.3.12.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getUserCount>
      <sessionID>0</sessionID>
    </ns:getUserCount>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.3.12.3. Return

- **user_count**, xsd:int

2.2.3.13. getUserBatch

2.2.3.13.1. Arguments

- **sessionID**, xsd:long
- **offset**, xsd:int
- **limit**, xsd:int

2.2.3.13.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getUserBatch>
      <sessionID>0</sessionID>
      <offset>0</offset>
      <limit>0</limit>
    </ns:getUserBatch>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.3.13.3. Return

- **users**, xsd:UserArray

2.2.4. Department Management

2.2.4.1. addDepartment

2.2.4.1.1. Arguments

- **sessionID**, xsd:long
- **department**, xsd:Department

2.2.4.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:addDepartment>
      <sessionID>0</sessionID>
      <department>
```

```

<departmentID>0</departmentID>
<departmentName></departmentName>
<departmentDescription></departmentDescription>
</department>
</ns:addDepartment>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.4.1.3. Return

- **departmentID**, xsd:int

2.2.4.2. updateDepartment

2.2.4.2.1. Arguments

- **sessionID**, xsd:long
- **departmentID**, xsd:int
- **department**, xsd:Department

2.2.4.2.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
<ns:updateDepartment>
<sessionID>0</sessionID>
<departmentID>0</departmentID>
<department>
<departmentID>0</departmentID>
<departmentName></departmentName>
<departmentDescription></departmentDescription>
</department>
</ns:updateDepartment>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.4.2.3. Return

- **status**, xsd:string

2.2.4.3. **getDepartments**

2.2.4.3.1. **Arguments**

- **sessionID**, xsd:long
- **departmentID**, xsd:int

2.2.4.3.2. **WSDL**

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getDepartments>
      <sessionID>0</sessionID>
      <departmentID>0</departmentID>
    </ns:getDepartments>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.4.3.3. **Return**

- **departments**, xsd:Department[]

2.2.4.4. **deleteDepartment**

2.2.4.4.1. **Arguments**

- **sessionID**, xsd:long
- **departmentID**, xsd:int

2.2.4.4.2. **WSDL**

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
```

```

<ns:deleteDepartment>
  <sessionID>0</sessionID>
  <departmentID>0</departmentID>
</ns:deleteDepartment>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.4.4.3. Return

- **status**, xsd:string

2.2.5. Access Group Management

2.2.5.1. addGroup

2.2.5.1.1. Arguments

- **sessionID**, xsd:long
- **group**, xsd:Group

2.2.5.1.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:addGroup>
      <sessionID>0</sessionID>
      <group>
        <groupID>0</groupID>
        <groupName></groupName>
        <departmentID>0</departmentID>
        <accessRight>
          <accessID>0</accessID>
          <terminalSN></terminalSN>
          <quickAccess>false</quickAccess>
          <timeSpec>
            <weekday>SUNDAY</weekday>
            <timePattern></timePattern>
          </timeSpec>

```

```

</accessRight>
</group>
</ns:addGroup>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.5.1.3. Return

- **groupID**, xsd:int

2.2.5.2. getGroups

2.2.5.2.1. Arguments

- **sessionID**, xsd:long
- **getGroupsCriteria**, xsd:getGroups

2.2.5.2.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getGroups>
      <sessionID>0</sessionID>
      <getGroupsCriteria>
        <groupID>0</groupID>
        <departmentID>0</departmentID>
      </getGroupsCriteria>
    </ns:getGroups>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.5.2.3. Return

- **groups**, xsd:Group[]

2.2.5.3. updateGroup

2.2.5.3.1. Arguments

- **sessionID**, xsd:long
- **groupID**, xsd:int

- **group**, xsd:Group

2.2.5.3.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:updateGroup>
      <sessionID>0</sessionID>
      <groupID>0</groupID>
      <group>
        <groupID>0</groupID>
        <groupName></groupName>
        <departmentID>0</departmentID>
        <accessRight>
          <accessID>0</accessID>
          <terminalSN></terminalSN>
          <quickAccess>false</quickAccess>
          <timeSpec>
            <weekday>SUNDAY</weekday>
            <timePattern></timePattern>
          </timeSpec>
        </accessRight>
      </group>
    </ns:updateGroup>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.5.3.3. Return

- **status**, xsd:string

2.2.5.4. deleteGroup

2.2.5.4.1. Arguments

- **sessionID**, xsd:long
- **groupID**, xsd:int

2.2.5.4.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:deleteGroup>
      <sessionID>0</sessionID>
      <groupID>0</groupID>
    </ns:deleteGroup>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.5.4.3. Return

- **status**, xsd:string

2.2.6. Trigger Maintenance Functions

2.2.6.1. getTriggers

2.2.6.1.1. Arguments

- sessionID, xsd:long
- getTriggersCriteria, xsd:getTriggersCriteria

2.2.6.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getTriggers>
      <sessionID>0</sessionID>
      <getTriggersCriteria>
        <triggerType>UNKNOWN</triggerType>
      </getTriggersCriteria>
    </ns:getTriggers>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```



```

<trigger>
  <triggerType>UNKNOWN</triggerType>
  <triggerName></triggerName>
  <timeSpec>
    <weekday>SUNDAY</weekday>
    <timePattern></timePattern>
  </timeSpec>
</trigger>
</ns:updateTrigger>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.6.2.3. Return

- **status**, xsd:string

2.2.6.3. clearTrigger

2.2.6.3.1. Arguments

- sessionID, xsd:long
- trigger, xsd:Trigger

2.2.6.3.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:clearTrigger>
      <sessionID>0</sessionID>
      <triggerType>UNKNOWN</triggerType>
    </ns:clearTrigger>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.6.3.3. Return

- **status**, xsd:string

2.2.7. Personal Functions

2.2.7.1. getMyself

2.2.7.1.1. Arguments

- **sessionID**, xsd:long

2.2.7.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getMyself>
      <sessionID>0</sessionID>
    </ns:getMyself>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.7.1.3. Return

- **user**, xsd:user

2.2.7.2. updateMyself

2.2.7.2.1. Arguments

- **sessionID**, xsd:long
- **user**, xsd:User

2.2.7.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:updateMyself>
      <sessionID>0</sessionID>
```

```

<user>
  <userID></userID>
  <lastName></lastName>
  <firstName></firstName>
  <otherName></otherName>
  <adminLevel>PERSONALUSER</adminLevel>
  <usePassword>>false</usePassword>
  <password></password>
  <groupID>0</groupID>
  <departmentID>0</departmentID>
  <fingerprintSecurityLevel>LOW</fingerprintSecurityLevel>
  <status>
    <active>>false</active>
    <autoMatch>>false</autoMatch>
    <smartCard>>false</smartCard>
    <fingerprint>>false</fingerprint>
    <password>>false</password>
  </status>
  <fingerprints
    <fingerprint>
      <image></image>
    </fingerprint>
  </fingerprints>
  <cardsn></cardsn>
</user>
</ns:updateMyself>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.7.2.3. Return

- **status**, xsd:string

2.2.8. Agent

2.2.8.1. registerAgent

2.2.8.1.1. Arguments

- **sessionID**, xsd:long
- **ip**, xsd:string
- **port**, xsd:int
- **agentVersion**, xsd:string

- **magic**, xsd:string
- **registrationID**, xsd:int
- **initSync**, xsd:boolean

2.2.8.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:registerAgent>
      <sessionID>0</sessionID>
      <ip></ip>
      <port>0</port>
      <agentVersion></agentVersion>
      <magic></magic>
      <registrationID></registrationID>
      <initSync>false</initSync>
    </ns:registerAgent>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.8.1.3. Return

- **status**, xsd:string

2.2.8.2. unregisterAgent

2.2.8.2.1. Arguments

- **sessionID**, xsd:long
- **ip**, xsd:string
- **port**, xsd:int

2.2.8.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```

xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:unregisterAgent>
    <sessionID>0</sessionID>
    <ip></ip>
    <port>0</port>
  </ns:unregisterAgent>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.8.2.3. Return

- **status**, xsd:string

2.2.8.3. getRegisteredAgents

2.2.8.3.1. Arguments

- **sessionID**, xsd:long

2.2.8.3.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getRegisteredAgents>
      <sessionID>0</sessionID>
    </ns:getRegisteredAgents>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.8.3.3. Return

- **agents**, xsd:Agent[]

2.2.9. Time Settings

2.2.9.1. getSNTP

Check if SNTP server is enabled or disabled

2.2.9.1.1. Arguments

- **sessionID**, xsd:long

2.2.9.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getSNTP>
      <ns:sessionID>0</ns:sessionID>
    </ns:getSNTP>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.9.1.3. Return

- **enable**, xsd:boolean
true if SNTP enabled, false if disabled

2.2.9.2. setSNTP

To enable or disable SNTP server

2.2.9.2.1. Arguments

- **sessionID**, xsd:long
- **enable**, xsd:boolean
true if SNTP enabled, false if disabled

2.2.9.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setSNTP>
      <ns:sessionID>0</ns:sessionID>
```

```

<ns:enable>false</ns:enable>
</ns:setSNTP>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.9.2.3. Return

- **status**, xsd:string

2.2.9.3. getSNTPServer

To get SNTP server IP address

2.2.9.3.1. Arguments

- **sessionID**, xsd:long

2.2.9.3.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getSNTPServer>
      <ns:sessionID>0</ns:sessionID>
    </ns:getSNTPServer>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.9.3.3. Return

- **serveraddr**, xsd:string
SNTP server IP address

2.2.9.4. setSNTPServer

To set SNTP server IP address

2.2.9.4.1. Arguments

- **sessionID**, xsd:long
- **serveraddr**, xsd:string
SNTP server IP address

2.2.9.4.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setSNTPServer>
      <ns:sessionID>0</ns:sessionID>
      <ns:serveraddr></ns:serveraddr>
    </ns:setSNTPServer>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.9.4.3. Return

- **status**, xsd:string
- errorSNTP server unreachable, if the address cannot be resolved.

2.2.9.5. *getTerminalDateTime*

To get date time in the terminal

2.2.9.5.1. Arguments

- **sessionID**, xsd:long

2.2.9.5.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getTerminalDateTime>
      <ns:sessionID>0</ns:sessionID>
    </ns:getTerminalDateTime>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.9.5.3. Return

- **seconds**, xsd:datetime
timestamp of terminal in UTC

2.2.9.6. setTerminalDateTime

To set date time in the terminal

2.2.9.6.1. Arguments

- **sessionID**, xsd:long
- **seconds**, xsd:datetime
timestamp of terminal in UTC

2.2.9.6.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setTerminalDateTime>
      <ns:sessionID>0</ns:sessionID>
      <ns:terminalDate></ns:terminalDate>
    </ns:setTerminalDateTime>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.9.6.3. Return

- **status**, xsd:string

2.2.9.7. getTimeZone

To get time zone in the terminal

2.2.9.7.1. Arguments

- **sessionID**, xsd:long

2.2.9.7.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
```

```

xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:getTimeZone>
    <ns:sessionID>0</ns:sessionID>
  </ns:getTimeZone>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.9.7.3. Return

- **timezone ID**, xsd:string
Olson timezone ID (see the table in Chapter 7)

2.2.9.8. setTimeZone

To get time zone in the terminal

2.2.9.8.1. Arguments

- **sessionID**, xsd:long
- **timezone ID**, xsd:string
Olson timezone ID (see the table in Chapter 7)

2.2.9.8.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setTimeZone>
      <ns:sessionID>0</ns:sessionID>
      <ns:timezone></ns:timezone>
    </ns:setTimeZone>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.9.8.3. Return

- **status**, xsd:string

2.2.10. Misc Functions**2.2.10.1. openDoor****2.2.10.1.1. Arguments**

- **sessionID**, xsd:long
- **doorID**, xsd:int

2.2.10.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:openDoor>
      <sessionID>0</sessionID>
      <doorID>0</doorID>
    </ns:openDoor>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.10.1.3. Return

- **status**, xsd:string

2.2.10.2. getAPIVersion**2.2.10.2.1. Arguments**

- NA

2.2.10.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">
```

```

xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:getAPIVersion>
</ns:getAPIVersion>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.10.2.3. Return

- **version**, xsd:string

2.2.10.3. getTerminalList

2.2.10.3.1. Arguments

- **sessionID**, xsd:long

2.2.10.3.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getTerminalList>
      <sessionID>0</sessionID>
    </ns:getTerminalList>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.10.3.3. Return

- **terminalList**, xsd:Terminal[]

2.2.10.4. getTerminalStatus

2.2.10.4.1. Arguments

- **sessionID**, xsd:long

2.2.10.4.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"

```

```

xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:getTerminalStatus>
    <sessionID>0</sessionID>
  </ns:getTerminalStatus>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.10.4.3. Return

- **terminalStatus**, xsd:terminalStatus[]

2.2.10.5. openRelay

2.2.10.5.1. Arguments

- **sessionID**, xsd:long
- **relayID**, ns:RelayID

2.2.10.5.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:openRelay>
      <sessionID>0</sessionID>
      <relayID>ONE</relayID>
    </ns:openRelay>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.10.5.3. Return

- **status**, xsd:string

2.2.10.6. closeRelay

2.2.10.6.1. Arguments

- **sessionID**, xsd:long

- **relayID**, ns:RelayID

2.2.10.6.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:closeRelay>
      <sessionID>0</sessionID>
      <relayID>ONE</relayID>
    </ns:closeRelay>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.10.6.3. Return

- **status**, xsd:string

2.2.11. Terminal Settings

2.2.11.1. setFPSecurityLevel

2.2.11.1.1. Arguments

- **sessionID**, xsd:long
- **fpSecurityLevel**, xsi:ns1:FingerprintSecurityLevel

2.2.11.1.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setFpSecurityLevel>
      <sessionID>0</sessionID>
      <ns:fpSecurityLevel>LOW</ns:fpSecurityLevel>
    </ns:setFpSecurityLevel>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.1.3. Return

- **status**, xsd:string

2.2.11.2. getFPSecurityLevel

2.2.11.2.1. Arguments

- **sessionID**, xsd:long

2.2.11.2.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getFpSecurityLevel>
      <sessionID>0</sessionID>
    </ns:getFpSecurityLevel>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.2.3. Return

- **fpSecurityLevel**, xsi:ns1:FingerprintSecurityLevel

2.2.11.3. setRelayOption

2.2.11.3.1. Arguments

- **sessionID**, xsd:long
- **relayID**, ns:RelayID
- **relayOpt**, ns:RelayOption

2.2.11.3.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setRelayOption>
      <sessionID>0</sessionID>
      <relayID>ONE</relayID>
      <relayOpt>RELAY-DISABLE</relayOpt>
    </ns:setRelayOption>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.3.3. Return

- **status**, xsd:string

2.2.11.4. getRelayOption

2.2.11.4.1. Arguments

- **sessionID**, xsd:long
- **relayID**, ns:RelayID

2.2.11.4.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
```

```

<ns:getRelayOption>
  <sessionID>0</sessionID>
  <relayID>ONE</relayID>
</ns:getRelayOption>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.11.4.3. Return

- **relayOpt**, ns:RelayOption

2.2.11.5. setRelayDelay

2.2.11.5.1. Arguments

- **sessionID**, xsd:long
- **relayID**, ns:RelayID
- **sec**, xsd:int

2.2.11.5.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setRelayDelay>
      <sessionID>0</sessionID>
      <relayID>ONE</relayID>
      <sec>0</sec>
    </ns:setRelayDelay>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.11.5.3. Return

- **status**, xsd:string

2.2.11.6. getRelayDelay

2.2.11.6.1. Arguments

- **sessionID**, xsd:long

- **relayID**, ns:RelayID

2.2.11.6.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getRelayDelay>
      <sessionID>0</sessionID>
      <relayID>ONE</relayID>
    </ns:getRelayDelay>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.6.3. Return

- **sec**, xsd:int

2.2.11.7. setAutoInOut

2.2.11.7.1. Arguments

- **sessionID**, xsd:long
- **auto_in_out_option**, xsi:ns1:AutoInOutOption

2.2.11.7.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setAutoInOut>
      <sessionID>0</sessionID>
      <ns:auto-in-out-option>DISABLE</ns:auto-in-out-option>
    </ns:setAutoInOut>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.7.3. Return

- **status**, xsd:string

2.2.11.8. getAutoInOut**2.2.11.8.1. Arguments**

- **sessionID**, xsd:long

2.2.11.8.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getAutoInOut>
      <sessionID>0</sessionID>
    </ns:getAutoInOut>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.8.3. Return

- **auto-in-out-option**, xsi:ns1:AutoInOutOption

2.2.11.9. setLogUnauthorizedEvent**2.2.11.9.1. Arguments**

- **sessionID**, xsd:long
- **enable**, xsd:boolean

2.2.11.9.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setLogUnauthorizedEvent>
```

```

<sessionID>0</sessionID>
<ns:enable>>false</ns:enable>
</ns:setLogUnauthorizedEvent>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.11.9.3. Return

- **status**, xsd:string

2.2.11.10. getLogUnauthorizedEvent

2.2.11.10.1. Arguments

- **sessionID**, xsd:long

2.2.11.10.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getLogUnauthorizedEvent>
      <sessionID>0</sessionID>
    </ns:getLogUnauthorizedEvent>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.11.10.3. Return

- **enable**, xsd:boolean

2.2.11.11. getCaptureFingerprint

2.2.11.11.1. Arguments

- **sessionID**, xsd:long

2.2.11.11.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"

```

```
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:getCaptureFingerprint>
    <sessionID>0</sessionID>
  </ns:getCaptureFingerprint>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.11.3. **Return**

- **jpegPhoto**, xsd: base64Binary

2.2.11.12. *initCaptureFP*

2.2.11.12.1. *Arguments*

- **sessionID**, xsd:long

2.2.11.12.2. *WSDL*

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:initCaptureFP>
      <sessionID>0</sessionID>
    </ns:initCaptureFP>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.11.12.3. *Return*

- **jpegPhoto**, xsd: base64Binary
- **status**, xsd:string

2.2.12. *Job Code*

2.2.12.1. *getJobCodeSettings*

2.2.12.1.1. *Arguments*

- **sessionID**, xsd:long

2.2.12.1.2. *WSDL*

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
```

```

<SOAP-ENV:Body>
  <ns:getJobCodeSettings>
    <sessionID>0</sessionID>
  </ns:getJobCodeSettings>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.12.1.3. Return

- **Jobcodesettings** : ns:JobCodeSettingsArray

2.2.12.2. updateJobCodeSettings

2.2.12.2.1. Arguments

- **sessionID**, xsd:long

2.2.12.2.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:updateJobCodeSettings>
      <sessionID>0</sessionID>
      <jobcodesettings>
        <jobcodesettings>
          <jobcode>0</jobcode>
          <jobcodeName></jobcodeName>
          <enable>0</enable>
        </jobcodesettings>
      </jobcodesettings>
    </ns:updateJobCodeSettings>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.12.2.3. Return

- **status**: xsd:string

2.2.12.3. addJobCodes

2.2.12.3.1. Arguments

- **sessionID** xsd:long
- **jobcodes** ns:JobCodeArray

2.2.12.3.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:addJobCodes>
      <sessionID>0</sessionID>
      <jobcodes>
        <jobcodes>
          <JobCodeID>0</JobCodeID>
          <JobCodeDescription></JobCodeDescription>
          <enable>0</enable>
          <jobCode>0</jobCode>
        </jobcodes>
      </jobcodes>
    </ns:addJobCodes>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.12.3.3. Return

- **status:** xsd:string

2.2.12.4. updateJobCodes

2.2.12.4.1. Arguments

- **sessionID** xsd:long
- **jobcodes** ns:JobCodeArray

2.2.12.4.2. WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
```

```

xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
  <ns:updateJobCodes>
    <sessionID>0</sessionID>
    <jobcodes>
      <jobcodes>
        <JobCodeID>0</JobCodeID>
        <JobCodeDescription></JobCodeDescription>
        <enable>0</enable>
        <jobCode>0</jobCode>
      </jobcodes>
    </jobcodes>
  </ns:updateJobCodes>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.12.4.3. Return

- **status:** xsd:string

2.2.12.5. deleteJobCodes

2.2.12.5.1. Arguments

- **sessionID** xsd:long
- **jobcodes** ns:JobCodeArray

2.2.12.5.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:deleteJobCodes>
      <sessionID>0</sessionID>

```

```

<jobcodes>
  <jobcodes>
    <JobCodeID>0</JobCodeID>
    <JobCodeDescription></JobCodeDescription>
    <enable>0</enable>
    <jobCode>0</jobCode>
  </jobcodes>
</jobcodes>
</ns:deleteJobCodes>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

2.2.12.5.3. Return

- **status:** xsd:string

2.2.12.6. getJobCodes

2.2.12.6.1. Arguments

- **sessionID** xsd:long
- **getJobCodeCriteria** ns:getJobCodeCriteria

2.2.12.6.2. WSDL

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getJobCodes>
      <sessionID>0</sessionID>
      <getJobCodeCriteria>
        <jobcodeID>0</jobcodeID>
        <jobcodeDescription></jobcodeDescription>
        <enable>0</enable>
        <jobcode>0</jobcode>
      </getJobCodeCriteria>
    </ns:getJobCodes>
  </SOAP-ENV:Body>

```

```
</SOAP-ENV:Envelope>
```

2.2.12.6.3. Return

- **jobcodes:** ns:JobCodeArray

2.2.13 Consent

2.2.13.1 getConsent

Arguments

- **sessionID,** xsd:long

2.2.13.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getConsent>
      <sessionID>0</sessionID>
    </ns:getConsent>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

• 2.2.13.3 Return

- **enable:** xsd:boolean -- true: enable, false:disable
- **display-name:** xsd:String -- display name for consent message.

2.2.13.3 setConsent

Arguments

- **sessionID,** xsd:long
- **enable:** xsd:boolean

- **display-name:** xsd:String
- **target:** xsd:String
- **fps:** RTPfps

2.2.13.4 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:setConsent>
      <sessionID>0</sessionID>
      <ns:enable>>false</ns:enable>
      <display-name></display-name>
    </ns:setConsent>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

- **2.2.13.3 Return**
 - Status : xsd:String

2.2.14 Log Setting

2.2.14.1 getgetLogSetting

Arguments

- **sessionID,** xsd:long

2.2.14.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
```

```

<ns:getLogSetting>
  <sessionID>0</sessionID>
</ns:getLogSetting>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

- **2.2.13.3 Return** : refer to ns LogSetting structure

- log-event: ns LogEvent
- log-size:
- log-unAuth-event
- log-Accept-nonRegistered-card
- log-photo-Auth-event
- log-photo-unAuth-event
- log-Accept-nonRegistered-facial
- log-case-event
- log-EM-Option

2.2.14.3 **setLogSetting**

Arguments

- **sessionID**, xsd:long
- logsetting: ns LogSetting

2.2.14.4 **WSDL**

```

<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
  <SOAP-ENV:Body>
    <ns:getLogSettingResponse>
      <response>
        <log-event>LOGEVENT-DISABLE</log-event>

```

```
<log-size>LOGS-10K</log-size>
<log-unAuth-event>>false</log-unAuth-event>
<log-Accept-nonRegistered-card>>false</log-Accept-nonRegistered-card>
<log-photo-Auth-event>>false</log-photo-Auth-event>
<log-photo-unAuth-event>>false</log-photo-unAuth-event>
<log-Accept-nonRegistered-facial>>false</log-Accept-nonRegistered-facial>
<log-case-event>>false</log-case-event>
<log-EM-Option>EM-LOG-FULL-SN</log-EM-Option>
</response>
</ns:getLogSettingResponse>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

- **2.2.14.5 Return**

- Status : xsd:String

Chapter 3. Creating C Application

3.1. Requirements

- Supported OS: Windows(win32/WinCE), Linux, Sun Solaris and Mac OS X
- gSOAP 2.7

3.2. Example

Assume IP address of ACTAtek is 192.168.1.112,

Makefile

```
CC=gcc
OBJS=soapC.o soapClient.o main.o
LIBS=-lgsoap
LDFLAGS=-O2 -s
CFLAGS=-O2 -I. -I/usr/local/include
#CFLAGS+=-DDEBUG

all: $(OBJS) main

ACTAtek.wsdl:
    wget http://192.168.1.112/soap/document/ACTAtek.wsdl

ACTAtek.h: ACTAtek.wsdl
    wsdl2h -c ACTAtek.wsdl

main: $(OBJS)
    $(CC) -o $@ $(OBJS) $(LIBS) $(LDFLAGS)

soapClient.c: ACTAtek.h
    soapcpp2 -c ACTAtek.h

soapC.c: ACTAtek.h
    soapcpp2 -c ACTAtek.h

%.o: %.c
    $(CC) $(CFLAGS) -c $<

%.o: %.cpp
    $(CPP) $(CFLAGS) -c $<
```

clean:

```
$(RM) -rf soapServerLib.* soapClientLib.* soapC.*
$(RM) -rf soapServer.* soapClient.* soapH.* soapStub.*
$(RM) -rf soap.* soapClient.* soapH.* soapStub.*
$(RM) -rf soapObject.h soapProxy.h
$(RM) -rf soapServiceObject.h soapServiceProxy.h
$(RM) -rf ws *ACTAtek*
$(RM) -rf *.xml *.xsd *.wsdl *.nsmmap
$(RM) -rf $(OBSJ) main
$(RM) -rf ns.h
$(RM) -rf *~
```

main.c

```
#include "soapH.h"           // obtain the generated stub
#include "ACTAtek.nsmmap"    // obtain the namespace mapping table

#define SOAP_CMD "http://192.168.1.142/cgi-bin/rpcrouter"

int main(int argc, char **argv)
{
    struct soap soap;       // gSOAP runtime environment
    soap_init(&soap);        // initialize runtime environment (only once)
    char *employeeID = NULL;
    if (argc == 2) {
        employeeID = argv[1];
    }

    // Try Login
    struct ns1__loginResponse response;
    printf("Calling...\n");
    if (soap_call_ns1__login(&soap, SOAP_CMD, NULL, "A999", \
        "1", &response) == SOAP_OK) {
        printf("Session ID: %d\n", response.ns1__sessionID);
    } else {                  // an error occurred
        soap_print_fault(&soap, stderr);
    }

    // Log search
    struct ns1__getLogsResponse getLogsResponse;
    struct ns1__getLogsCriteria lcriteria;
```

```

memset(&criteria, 0, sizeof(criteria));
lcriteria.employeeID = employeeID;
if (soap_call_ns1__getLogs(&soap, SOAP_CMD, NULL, \
    response.ns1__sessionID, &lcriteria, \
    &getLogsResponse) == SOAP_OK) {
    if (getLogsResponse.ns1__logs) {
        int size = getLogsResponse.ns1__logs->__sizelog;
        printf("No of Logs: %d\n", size);
        int i = 0;
        for (i = 0; i < size; i++) {
            printf(" LogID: %d", getLogsResponse.ns1__logs->log[i]->logID);
            printf(", User: %s", getLogsResponse.ns1__logs->log[i]->userID);
            printf(", Trigger: %d", getLogsResponse.ns1__logs->log[i]->trigger);
            printf(", Timestamp: %s", ctime(&(getLogsResponse.ns1__logs-
>log[i]->timestamp)));
        }
    }
} else { // an error occurred
    soap_print_fault(&soap, stderr);
}

// Try Logout
struct ns1__logoutResponse oresponse;

if (soap_call_ns1__logout(&soap, SOAP_CMD, NULL, \
    response.ns1__sessionID, \
    &oreponse) == SOAP_OK) {
    printf("LOGOUT Session ID: %d\n", response.ns1__sessionID);
} else{ // an error occurred
    soap_print_fault(&soap, stderr);
}

soap_destroy(&soap); // delete deserialized class instances (for C++ only)
soap_end(&soap); // remove deserialized data and clean up
soap_done(&soap); // detach the gSOAP environment
return 0;
}

```

Chapter 4. Creating Visual Basic Application

4.1. Requirements

- Supported OS: Windows 98, ME, 2000, XP
- SOAP Toolkit 3.0 for Windows
- Visual Basic 6.0

4.2. Example

```

Private Sub login()
    Dim Serializer As SoapSerializer30
    Dim Connector As SoapConnector30
    Dim Reader As SoapReader30
    Dim str As String
    Dim newline As String
    Dim name As String
    Dim password As String

    On Error GoTo End_this_process      ' Prevent the mistype of IP address

    Set Connector = New HttpConnector30
    Connector.Property("EndPointURL") = "http://" & Text3.Text & "/cgi-bin/rpcrouter"
    Connector.Connect

    Connector.BeginMessage

    Set Serializer = New SoapSerializer30
    Serializer.Init Connector.InputStream

    Serializer.StartEnvelope "", "STANDARD"
    Serializer.SoapNamespace "xsi", "http://www.w3.org/2001/XMLSchema-instance"
    Serializer.SoapNamespace "xsd", "http://www.w3.org/2001/XMLSchema"
    Serializer.SoapNamespace "ns1", "http://www.hectrix.com/ACTAtek.xsd"

    Serializer.StartBody
    Serializer.StartElement "ns1:login"

    name = Text1.Text

```

```
password = Text2.Text

Serializer.StartElement "username"
Serializer.WriteString name
Serializer.EndElement
Serializer.StartElement "password"
Serializer.WriteString password
Serializer.EndElement

Serializer.EndElement
Serializer.EndBody
Serializer.EndEnvelope

Connector.EndMessage

' The following lines show how you would retrieve a result if the method returned one
Set Reader = New SoapReader30
Reader.Load Connector.OutputStream

str = Reader.RpcResult.Text

sessionID = Val(str)

If sessionID = 0 Then      'sessionID received, login success
    status.Caption = "Login Failed"
End If

End_this_process:
End Sub
```

Chapter 5. Creating .NET Application

5.1. Requirements

- Supported OS: 2000, XP
- Visual Studio .NET 2003

5.2. Example

Create the Web Reference using the ACTAtek.WSDL located on the terminal at

```
http://<deviceIP>/soap/document/ACTAtek.wsdl
```

This will automatically generate all the methods to access the ACTAtek API.

```
Private Sub Login()
    ' Login SOAP request
    Dim sessionID As Long
    Dim IP_Addr As String
    Dim UserID As String
    Dim Password As String
    IP_Addr="192.168.1.100"
    UserID ="A999"
    Password="1"

    Try
        ' ACTAtekWSDL is the name of the web reference
        Dim ActaService As ACTAtekWSDL.ACTAtek =New ACTAtekWSDL.ACTAtek
        ActaService.Url = "http://" & IP_Addr & "/cgi-bin/rpcrouter"
        sessionID = ActaService.login(UserID, Password)

        Catch ex As Exception
            MsgBox(ex.Message)
        End Try
    End Sub
```

Sample Code to get detail event log, Session ID is obtained from the login API request

```

Private Sub GetFullLog()
' GetFullLog SOAP Request
Dim dateFrom As Date
Dim dateTo As Date
Dim EventTrigger As ACTAtetekWSDL.triggerType
Dim Trigger As String
Dim IP_Addr As String

IP_Addr="192.168.1.100"

' Get the Event Trigger
Trigger = "IN"
' Retrieve Enum from its member name (Event Trigger name)
EventTrigger=CType(System.Enum.Parse(GetType(ACTAtetekWSDL.
    triggerType), Trigger), ACTAtetekWSDL.triggerType)
'parse string date into date format
dateFrom = DateTime.Parse( "01/01/00 00:00:01")
dateTo = Now

Dim ActaService As ACTAtetekWSDL.ACTAtetek = New ACTAtetekWSDL.ACTAtetek
ActaService.Url = "http://" & IP_Addr & "/cgi-bin/rpcrouter"

Dim LogCriteria As ACTAtetekWSDL.getLogCriteria
' Set the getLogsCriteria
LogCriteria = New ACTAtetekWSDL.getLogCriteria
LogCriteria.from = dateFrom 'Date
LogCriteria.to = dateTo 'Date
LogCriteria.departmentID = 0 ' Integer
LogCriteria.departmentIDSpecified = False ' Boolean
LogCriteria.employeeID = "" ' String
LogCriteria.employeeName = "" 'String
LogCriteria.fromSpecified = True ' Boolean
LogCriteria.toSpecified = True ' Boolean
LogCriteria.trigger = EventTrigger ' Eventtype
LogCriteria.triggerSpecified = False ' Boolean
LogCriteria.terminaSN="" ' String

```

```

' get the output from getlog
Dim Logs() As ACTAtekWSDL.LogDetail
Dim log As ACTAtekWSDL.LogDetail
Dim count As Integer
Dim textLog As String

Logs = ActaService.getFullLogs(SessionID, LogCriteria, 1, False)
' Check if anything is retrieved
If Logs Is Nothing Then
    ' No log retrieved so exit sub
    Exit Sub
End If

txtOutput.Text = ""
count = 0
'Go through each log
For Each log In Logs
    count = count + 1
    'retrieve an Enum member (Event Trigger name),
    'cast the integer value from log.trigger to your Enum type
    EventTrigger = CType(log.trigger, ACTAtekWSDL.triggerType)
    textLog = textLog & count & ": " & log.userName & " " & log.userID &
        " " & log.timestamp & " " & log.departmentName &
        " " & EventTrigger.ToString & " " & log.terminalName &
        " " & log.terminalSN & " " & log.remark & vbCrLf
Next

txtOutput.Text = textLog

End Sub

```

Chapter 6. Creating JAVA Application

6.1. Requirements

- Apache AXIS (Java) 1.1 or later

6.2. Example

Creating Java Proxy class,

```
$ java org.apache.axis.wsdl.WSDL2Java
http://<deviceIP>/soap/document/ACTAtek.wsdl
```

It will generate the Java Proxy class and related data structures/classes that used to access the service. The generated Proxy should be used to call the remote service. You can find the proxy in the package:

```
com.hectrix.www.ACTAtek_service
```

There is a ACTAtekLocator.java generated, which can be used locate the service provided by a particular location (URL, or Service Endpoint). Sample Calling Sequence of the Login function:

```
ACTAtekLocator locator = new ACTAtekLocator();
ACTAtekPortType api = locator.getACTAtek(new
java.net.URL("http://192.168.1.100/cgi-bin/rpcrouter"));
long sessionID = api.login("A123", "123");
```

You should change the IP address appropriately to reflect the actual deployment setting of your ACTAtek. As you can see, "api" object is used to access the remote methods exposed by WSDL. Please refer to the [API] section for details of the methods provided.

For issues related the generation of Java Proxy, please refer to the Apache website. (<http://ws.apache.org>)

Makefile

```
JAVA_HOME=/usr/java
JAVA=$(JAVA_HOME)/bin/java
JAVAC=$(JAVA_HOME)/bin/javac

WSDL_URL=http://192.168.1.112/soap/document/ACTAtek.wsdl

CLASSPATH=lib/axis.jar:lib/jaxrpc.jar:lib/saaj.jar:lib/commons-logging.jar:lib/commons-discovery.jar:lib/wsdl4j.jar
WSDL2JAVA=$(JAVA) -classpath $(CLASSPATH) org.apache.axis.wsdl.WSDL2Java
```

```

all: generate_java_classes Main.class

Main.class: Main.java .PROXY_GENERATED
    $(JAVAC) -classpath ..$(CLASSPATH) Main.java

runtest: Main.class .PROXY_GENERATED
    $(JAVA) -classpath ..$(CLASSPATH) Main

generate_java_classes: .PROXY_GENERATED

.PROXY_GENERATED:
    $(WSDL2JAVA) $(WSDL_URL)
    touch .PROXY_GENERATED

clean:
    rm -rf *.class com *~ .PROXY_GENERATED

```

Main.java

```

import com.hectrix.www.ACTAtek_service.*;

/*
 * Sample Calling Sequence of the Login function:
 */
public class Main {

    public static void main(String args[]) throws Exception {
        ACTAtekLocator locator = new ACTAtekLocator();
        ACTAtekPortType api = locator.getACTAtek(
            new java.net.URL("http://192.168.1.112/cgi-bin/rpcrouter"));
        long sessionID = api.login("A999", "1");
        System.out.println("SessionID="+sessionID);
        api.logout(sessionID);
    }
}

```

Chapter 7. Using SOAP API with SSL

7.1. Requirements

- Supported OS: Windows(win32/WinCE), Linux, Sun Solaris and Mac OS X
- gSOAP 2.7
- stdsoap2.c stdsoap2.h from gSOAP package

7.2. Example

Assume IP address of ACTAtek is 192.168.1.112,

Makefile

```
CC=gcc
OBJS=soapC.o soapClient.o main.o stdsoap2.o
LIBS=-lgsoap -lssl -lcrypto
LDFLAGS=-O2 -s
CFLAGS=-O2 -I. -I/usr/local/include
#CFLAGS+=-DDEBUG
CFLAGS+=-DDEBUG -DWITH_OPENSSL

all: $(OBJS) main

ACTAtek.wsdl:
    wget http://192.168.1.112/soap/document/ACTAtek.wsdl

ACTAtek.h: ACTAtek.wsdl
    wsdl2h -c ACTAtek.wsdl

main: $(OBJS)
    $(CC) -o $@ $(OBJS) $(LIBS) $(LDFLAGS)

soapClient.c: ACTAtek.h
    soapcpp2 -c ACTAtek.h

soapC.c: ACTAtek.h
    soapcpp2 -c ACTAtek.h

%.o: %.c
    $(CC) $(CFLAGS) -c $<
```

```

%.o: %.cpp
    $(CPP) $(CFLAGS) -c $<

clean:
    $(RM) -rf soapServerLib.* soapClientLib.* soapC.*
    $(RM) -rf soapServer.* soapClient.* soapH.* soapStub.*
    $(RM) -rf soap.* soapClient.* soapH.* soapStub.*
    $(RM) -rf soapObject.h soapProxy.h
    $(RM) -rf soapServiceObject.h soapServiceProxy.h
    $(RM) -rf ws *ACTAtek*
    $(RM) -rf *.xml *.xsd *.wsdl *.nsmmap
    $(RM) -rf $(OBSJ) main
    $(RM) -rf ns.h
    $(RM) -rf *~

```

main.c

```

#include "soapH.h"           // obtain the generated stub
#include "ACTAtek.nsmmap"    // obtain the namespace mapping table

#ifdef WITH_OPENSSL
    #define SOAP_CMD "https://192.168.1.142/cgi-bin/rpcrouter"
#else
    #define SOAP_CMD "http://192.168.1.142/cgi-bin/rpcrouter"
#endif

int main(int argc, char **argv)
{
    struct soap soap;      // gSOAP runtime environment
    soap_init(&soap);       // initialize runtime environment (only once)

#ifdef WITH_OPENSSL
    printf("Before SSL init\n");
    if (soap_ssl_client_context(&soap,
        SOAP_SSL_NO_AUTHENTICATION, // SOAP_SSL_DEFAULT,
        NULL, /* keyfile: required only when client must authenticate to server (see
        SSL docs on how to obtain this file) */
        NULL, /* password to read the key file */
        NULL, /* optional cacert file to store trusted certificates */
        NULL, /* optional capath to directoy with trusted certificates */
        NULL /* if randfile!=NULL: use a file with random data to seed random */
    )) {

```

```

        soap_print_fault(&soap, stderr);
        exit(1);
    }
    printf("After SSL init\n");
#endif

char *employeeID = NULL;
if (argc == 2) {
    employeeID = argv[1];
}

// Try Login
struct ns1__loginResponse response;
printf("Calling...\n");
if (soap_call_ns1__login(&soap, SOAP_CMD, NULL, "A999", \
    "1", &response) == SOAP_OK) {
    printf("Session ID: %d\n", response.ns1__sessionID);
} else {
    // an error occurred
    soap_print_fault(&soap, stderr);
}

// Log search
struct ns1__getLogsResponse getLogsResponse;
struct ns1__getLogsCriteria lcriteria;
memset(&lcriteria, 0, sizeof(criteria));
lcriteria.employeeID = employeeID;
if (soap_call_ns1__getLogs(&soap, SOAP_CMD, NULL, \
    response.ns1__sessionID, &lcriteria, \
    &getLogsResponse) == SOAP_OK) {
    if (getLogsResponse.ns1__logs) {
        int size = getLogsResponse.ns1__logs->__sizelog;
        printf("No of Logs: %d\n", size);
        int i = 0;
        for (i = 0; i < size; i++) {
            printf(" LogID: %d", getLogsResponse.ns1__logs->log[i]->logID);
            printf(", User: %s", getLogsResponse.ns1__logs->log[i]->userID);
            printf(", Trigger: %d", getLogsResponse.ns1__logs->log[i]->trigger);
            printf(", Timestamp: %s", ctime(&(getLogsResponse.ns1__logs-
>log[i]->timestamp)));
        }
    }
}

```

```
} else {           // an error occurred
    soap_print_fault(&soap, stderr);
}

// Try Logout
struct ns1__logoutResponse oresponse;

if (soap_call_ns1__logout(&soap, SOAP_CMD, NULL, \
    response.ns1__sessionID, \
    &oreponse) == SOAP_OK) {
    printf("LOGOUT Session ID: %d\n", response.ns1__sessionID);
} else{           // an error occurred
    soap_print_fault(&soap, stderr);
}

soap_destroy(&soap); // delete deserialized class instances (for C++ only)
soap_end(&soap);     // remove deserialized data and clean up
soap_done(&soap);    // detach the gSOAP environment
return 0;
}
```

Appendix A: Door Open Schedule

2.1.43. DoorOpenScheduleArray

Element	Type	Description
ptrtimespec	ns:Timespec	Array of Timespec
size	xsd : int	Size of Array

Table 42. DoorOpenScheduleArrayData Type Definition

2.2.14 DoorOpenSchedule

2.2.14.1 getDoorOpenScheduleArray

2.2.14.1.1 Arguments

sessionID, xsd:long

2.2.14.1.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
<ns:getDoorOpenSchedule>
<sessionID>0</sessionID>
</ns:getDoorOpenSchedule>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.14.1.3 Return

getDoorOpenSchedule: ns:DoorOpenScheduleArray

2.2.14.2 setDoorOpenSchedule

2.2.14.2.1 Arguments

sessionID, xsd:long

setDoorOpenScheduleArray, xsd:DoorOpenScheduleArray

2.2.14.2.2 WSDL

```
<?xml version="1.0" encoding="UTF-8"?>
<SOAP-ENV:Envelope
xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENC="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:ns="http://www.hectrix.com/ACTAtek.xsd">
<SOAP-ENV:Body>
<ns:setDoorOpenSchedule>
<sessionID>0</sessionID>
<setDoorOpenScheduleArray>
<timeSpec>
<weekday>SUNDAY</weekday>
<timePattern></timePattern>
</timeSpec>
</setDoorOpenScheduleArray>
</ns:setDoorOpenSchedule>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

2.2.14.2.3 Return

status: xsd:string

Appendix B: Added a new element in the ns:User structure

Added a new element in the ns:User structure

```
<facialrecords>  
  <facial>  
    <FacialTemplateType> ?</FacialTemplateType>  
    <FacialTemplate>?</FacialTemplate>  
  </facial>  
</facialrecords>
```